



2026 Owner's Manual

COAST FRESHE COLD PLUNGE RESIDENTIAL

Coast Spas Manufacturing
6315 202 Street Langley, BC Canada V2Y 1N1
info@coastspas.com
www.coastspas.com



COAST FRESHE COLD PLUNGE RESIDENTIAL

At Coast Spas, we're dedicated to enhancing your health and wellness through our Hot Tubs, Swim Spas, and Coast Freshe Cold Plunges. Built with advanced technology and trusted quality, our products are designed to help you relax, recover, and feel your best every day.

We're proud to be known for crafting the World's Best Built Spas®, and our Coast Freshe Cold Plunge Residential is a standout choice for boosting recovery and improving circulation. Whether for personal relaxation, therapy, or shared moments with loved ones, our units are made to enrich your life year-round.

We hope you enjoy the comfort, performance, and well-being our products bring for many years to come. Thank you for choosing Coast Spas.

CONGRATULATIONS!



**YOU'RE ALMOST READY TO ENJOY YOUR NEW COAST FRESHE COLD PLUNGE
RESIDENTIAL!**

COAST FRESHE COLD PLUNGE RESIDENTIAL



CONGRATULATIONS!

YOU'RE ALMOST READY TO ENJOY YOUR NEW UNIT!

Before you begin to enjoy your Coast Freshe Cold Plunge Residential, please take a moment to submit your warranty. For registering your Coast Freshe Cold Plunge Residential, you will need the serial number. The sample picture below will help you locate the serial number.



You can register your unit by using the link below. <https://coastspas.microsoftcrmportals.com/>



FOR YOUR REFERENCE

Owner's name: _____

Address: _____

Contact: _____	Email: _____
Serial number: _____	Purchase Date: _____
Delivery Date: _____	Dealer Name: _____

Contact your spa selling dealer if you have any queries related to your Coast Freshe Cold Plunge Residential. Coast Spas authorized dealers are trained professionals who can assist you with parts, set up, operations, maintenance, and technical support.

DISCLAIMER: At the time of print, this manual is accurate in its information. Coast Spas reserves the rights to change or modify any unit designs and/or features without notification. To check on updates or for other information, please visit www.coastspas.com

COAST FRESHE COLD PLUNGE RESIDENTIAL

UNLOADING AND UNBOXING INSTRUCTIONS

SAFETY FIRST

Your Coast Freshe Cold Plunge is large and heavy, improper handling may lead to injury or product damage. Please review the following safety guidelines before unloading.

General Safety

- Team Lift Only. It requires two or more people to lift or move. Never attempt to lift alone.
- Wear Safety Gloves & Footwear. Protect hands from sharp edges and feet from impact injuries.
- Do Not Drop or Tip Over. May cause damage to the structure or internal components.
- Keep Children & Pets Clear. Keep the area clear during unboxing and set up.
- Use Proper Lifting Techniques. Bend at the knees, not the waist. Keep your back straight.
- Lift from Designated Points. Only lift from stable, reinforced areas indicated on the box.

Handling Tip

- Use Built-In Plastic Handles. Your cold plunge is packaged with two plastic handles, one at the front and one at the back of the box. These handles are designed to assist with lifting and maneuvering the unit safely.
- Do not lift from the sides of the box or attempt to drag the unit.

Equipment Safety

- Use tools like pallet jack, dolly, or forklift if available.
- Do not use straps around the unit body for lifting. They may compress or deform the shell.

UNLOADING INSTRUCTIONS

Prepare the Area: Clear a space wide enough to maneuver the unit. Confirm the drop-off location is level and safe for unloading.

Inspect Upon Delivery: Before signing the delivery receipt, inspect the box and pallet for damage. Take photos of any damage and note it on the delivery form.

Unloading Options:

- With Equipment: Use a forklift or pallet jack to move the product safely.

- Without Equipment: Have 2–4 people lift using the plastic handles at the front and back.
- Avoid dragging or rolling unless specified as safe by the manufacturer.

UNBOXING INSTRUCTIONS

Remove Outer Packaging: Use a box cutter or scissors with caution, do not cut too deep. Remove shrink wrap, straps, and foam padding.

Check Package Content: Make sure the Coast Freshe Cold Plunge Residential is the correct color and came with the ordered accessories.

Inspect the Product: Look for dents, cracks, or missing components. Contact your dealer within 48 hours if anything is missing or damaged.

Dispose of Packaging Safely: Do not leave plastic wrap or foam where it could be a tripping hazard. Recycle where possible.

QUICK TIPS:

- If the unit is not installed immediately, store upright on a flat surface.
- Do not expose the unboxed unit to direct sunlight or rain until it's installed.
- Keep the serial number (usually located on the inside lip) for your warranty records.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COVER INSTALLATION INSTRUCTIONS

1. Position the Cover
 - Place the cover evenly over the Coast Freshe Cold Plunge Residential, ensuring the hinge aligns with the center for proper folding.
2. Attach Locking Clips Using Adhesive
 - Use high-strength double-sided adhesive tape (such as 3M VHB) to secure the locking clips to the acrylic cabinet.
 - Clean the surface thoroughly with isopropyl alcohol before applying tape for maximum adhesion.
 - Press clips firmly and allow adhesive to cure for at least 24 hours before applying tension.
3. Install Locking Straps
 - Attach straps to the clips and adjust for a snug fit.
 - Test the lock mechanism to ensure proper engagement.

Safety Note: Always lock the cover when not in use to prevent unauthorized access and reduce heat transfer.

SAFETY COVER CLIP INSTALLATION

This unit uses adhesive cover clips instead of screws. Do not drill into the unit acrylic, because this can crack or damage the surface.

Installation steps

1. Place the cover on the unit first and make sure it seals the unit perfectly.
2. Pull each strap down to find the exact clip location.
3. Ensure unit acrylic surface is clean and dry.
4. Remove the white paper from the adhesive backing on the cover lip.
5. Position the clip on the unit acrylic.
6. Press the clip firmly with your palm so the adhesive bonds to the acrylic.
7. Hold the clip under pressure for a few minutes before attaching the cover strap.

WARNING: Do not use screws or drill into the unit acrylic. This may cause permanent damage to the unit surface.



COAST FRESHE COLD PLUNGE

OWNER'S MANUAL

RESIDENTIAL

2026

TABLE OF CONTENTS

Cover Page	Page	1
Thank You Letter from Coast Spas	Page	2
Registering Your Coast Freshe Cold Plunge Residential	Page	3
Unloading and Unboxing Instructions	Page	4
Cover and Safety Cover Clip Installation Instructions	Page	5
Table of Contents	Page	6-7
Basic Information and Coast Freshe Cold Plunge Residential Surface & Transportation	Page	8-9
Important Safety Instructions	Page	10-12
Coast Freshe Cold Plunge Residential White Chiller Basic Operation	Page	13-15
Coast Freshe Cold Plunge Residential White Chiller Quick Reference Guide	Page	16-18
Coast Freshe Cold Plunge Residential White Chiller Smart Control App Set up	Page	19
Coast Freshe Cold Plunge Residential Black Chiller Basic Operation & Control Panel Interface	Page	20-22
Coast Freshe Cold Plunge Residential Black Chiller Quick Reference Guide	Page	23
Coast Freshe Cold Plunge Residential Black Chiller Smart Control App Set up	Page	24-31
Coast Freshe Cold Plunge Residential Chiller Troubleshooting Guide	Page	32-34
Glossary of Terms	Page	35
Coast Freshe Cold Plunge Residential General Layout	Page	36
Coast Freshe Cold Plunge Residential Specification	Page	37
Coast Freshe Cold Plunge Residential Care Guide	Page	38
Chemicals	Page	39-40

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

Chemical Handling Safety	<i>Page</i>	41-42
Warranty and Maintenance and Cover Care	<i>Page</i>	43
Public Health and Infection Control	<i>Page</i>	44
Coast Freshe Cold Plunge Residential Set up Guide	<i>Page</i>	45-46
Coast Freshe Cold Plunge Residential Water Care	<i>Page</i>	47-50
Water Clarity Troubleshooting	<i>Page</i>	51
Draining and Winterizing	<i>Page</i>	52-53
Auto Dosing System	<i>Page</i>	54
Sand Filter Installation	<i>Page</i>	55
Coast Freshe Cold Plunge Residential How-To Videos	<i>Page</i>	56
Coast Freshe Cold Plunge Residential Service Log	<i>Page</i>	57-59

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026



PLEASE READ YOUR ENTIRE OWNER'S MANUAL BEFORE UNIT OPERATION



Basic Information

Water Care

IMPORTANT: Caring for your water by ensuring proper chemical usage is the single most important thing you can do to keep your Coast Freshe Cold Plunge Residential in good condition.

WARNING: Improper chemical usage and maintenance will quickly lead to severe issues with your Coast Freshe Cold Plunge Residential and can affect the equipment, jets, pumps, and all other components in contact with the water.

All units are susceptible to damage from unbalanced water.

Electrical

All self contained units use 110VAC electrical spa packs.

110VAC: requires an isolated 15 Amp circuit breaker, an isolated circuit with no other appliances or lights on the circuit at any time. Extension cords are not to be used in conjunction with the operations of the Coast Freshe Cold Plunge Residential. Low voltage damage could result, and this is not covered under warranty.

IMPORTANT: Coast Freshe Cold Plunge Residential operates with 110V - 120V.

NOTE: All components must be 110V. No 240V allowable.

The electrical circuit must be installed by a certified electrician and approved by a local building or electrical inspector.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026



PLEASE READ YOUR ENTIRE OWNER'S MANUAL BEFORE UNIT OPERATION



Basic Information

Surface

Your new portable Coast Freshe Cold Plunge Residential must be placed on a firm, flat, and level surface, so that the weight is supported uniformly. Wood decking or balconies must be constructed to support a total weight of 1500 lbs. Refer to the local and current building codes in your area. Should your new Coast Freshe Cold Plunge Residential need to go through the gate or space – restricted area, ensure you've communicated those limitations with your dealer to avoid delivery complications.

NOTE: Damage caused by alternate decking methods may void the Coast Freshe Cold Plunge Residential warranty. Contact your dealer if you have any questions regarding location and placement.

Transport

Your new Coast Freshe Cold Plunge Residential has left the factory cleaned and polished and ready to begin operation after passing our many quality and operational tests. However, depending on your location in the world, your Coast Freshe Cold Plunge Residential may have spent days or even weeks in transit before arriving at your location. Please ensure that before filling up or operating your Coast Freshe Cold Plunge Residential that you check all electrical and plumbing connections are securely connected in the equipment area as they might have loosened during shipping. If any dirt has accumulated, you will want to remove it with a clean cloth or sponge using warm water.

Disclaimer: Coast Spas is not responsible for any damage to the Coast Freshe Cold Plunge Residential unit that may occur because of improper loading, unloading, or transport method on a customer's or delivery vehicle. Additionally, any injuries sustained during the lifting, moving, or handling of the Coast Freshe Cold Plunge Residential unit are the sole responsibility of the customer. It is strongly recommended to use proper lifting techniques and sufficient manpower or equipment when transporting the unit to avoid damage or injury.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

IMPORTANT SAFETY INSTRUCTIONS

bonded to the equipment grounding buss with copper conductors not smaller than No. 6 AWG.

READ AND FOLLOW ALL INSTRUCTIONS CAREFULLY

⚠ DANGER: Risk of Injury. The suction fittings in this Coast Freshe Cold Plunge Residential are sized to match the specific water flow created by the pump. Never operate the Coast Freshe Cold Plunge Residential if the suction fittings are broken or missing. Never replace a suction fitting with one rated less than the flow rate marked on the original suction fitting.

⚠ DANGER: Risk of Accidental Drowning. Do not allow children to be in or around Coast Freshe Cold Plunge Residential. Keep the Coast Freshe Cold Plunge Residential cover on and secure when not in use.

⚠ DANGER: Risk of Electrical Shock. The electrical supply for this product must include a suitably rated switch or circuit breaker to open all ungrounded supply conductors to comply with section 422-20 of the National Electrical Code, ANSI/NFPA 70. The disconnect must be readily accessible and visible to the Coast Freshe Cold Plunge Residential occupant but installed at least 5 feet (1.5 m) from the Coast Freshe Cold Plunge Residential water.

READ, FOLLOW AND SAVE THESE INSTRUCTIONS

- a) A green colored terminal or a terminal marked G, Gr, Ground, Grounding or the symbol * is located inside the supply terminal box or compartment. To reduce the risk of electric shock, this terminal must be connected to the grounding means provided in the electric supply service panel with a continuous copper wire equivalent in size to the circuit conductors that supply this equipment.
- b) At least two lugs marked "Bonding Lugs" are provided on the external surface or on the inside of the supply terminal box compartment. To reduce the risk of electric shock, connect the local common bonding grid in the area of the unit to these terminals with an insulated or bare copper conductor not smaller than No. 6 AWG.
- c) All field-installed metal components such as rails, ladders, drains or other similar hardware within 5 feet (1.5 m) of the unit shall be

⚠ WARNING: Only use this product with 120V/60Hz electrical circuit; outlet must be grounded.

⚠ WARNING: Do not permit electric appliances (such as lights, telephone, radio, television, etc.) to be within 5 feet (1.5m) of this Coast Freshe Cold Plunge Residential.

⚠ CAUTION: Connect only to a circuit protected by a Class A ground fault circuit interrupter or residual current device.

⚠ CAUTION: To ensure continued protection against shock hazard, use only identical replacement parts when servicing.

⚠ CAUTION: Test the ground fault circuit interrupter before each use of the Coast Freshe Cold Plunge Residential.

⚠ CAUTION: Read the instruction manual.

⚠ WARNING: Children should not use the Coast Freshe Cold Plunge Residential without adult supervision.

⚠ WARNING: Do not use the Coast Freshe Cold Plunge Residential unless all suction guards are installed to prevent body and hair entrapment.

⚠ WARNING: People with infectious diseases should not use a Coast Freshe Cold Plunge Residential.

⚠ WARNING: People using medication and/or having an adverse medical history should consult a physician before using the Coast Freshe Cold Plunge Residential.

⚠ WARNING: Do not use the Coast Freshe Cold Plunge Residential immediately following strenuous exercise.

⚠ WARNING: Prolonged immersion in the Coast Freshe Cold Plunge Residential may be injurious to your health.

⚠ WARNING: Do not operate below 50 °F (10 °C) without a winterization plan. Extended exposure to cold water can cause hypothermia and cardiac distress. Review the important Hypothermia signs and symptoms listed below.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

Hypothermia Safety

Extended exposure to cold water can cause the body's temperature to drop below normal, leading to hypothermia. While cold water immersion can be beneficial in moderation, prolonged exposure can be dangerous if the body cannot maintain its natural warmth.

How the Body Loses Heat

The body loses heat through:

- **Conduction** – direct contact with cold surfaces or water.
- **Convection** – moving water or air around the body.
- **Radiation** – heat escaping from the skin.
- **Evaporation** – moisture on the skin cooling the body.

If the body's natural warming mechanisms, like shivering, are no longer effective, hypothermia can occur.

WARNING

- **Mild Hypothermia:** Shivering, goosebumps, slight loss of coordination.
- **Moderate Hypothermia:** Intense shivering, slurred speech, sluggish movements, impaired motor skills.
- **Severe Hypothermia:** Rigid muscles, confusion, loss of shivering, blue or pale skin, irregular heartbeat, or loss of consciousness.

What to Do:

- Exit the cold water immediately.
- Warm the body gradually using blankets or warm clothing.
- Seek medical attention if symptoms are severe.

! **Important:** Always monitor your exposure time in cold water and never exceed safe limits.


WARNING

! No Diving or Jumping

- To prevent injury, never dive or jump into the unit.

! For Trained Personnel Only

- Commercial use requires trained staff. Maintain water-testing logs for compliance and safety.



COAST FRESHE COLD PLUNGE RESIDENTIAL

⚠ CAUTION: Adequate drainage and ventilation must be provided if the equipment is to be installed in a pit.

⚠ CAUTION: When using this electrical equipment, basic safety precautions should always be followed.

⚠ WARNING: To avoid injury, exercise care when entering or exiting the Coast Freshe Cold Plunge Residential.

⚠ WARNING: Do not use drugs or alcohol before or during the use of the Coast Freshe Cold Plunge Residential to avoid unconsciousness and possible drowning. The use of alcohol or drugs can greatly increase the risk of fatal hypothermia in the Coast Freshe Cold Plunge Residential.

⚠ WARNING: Pregnant or possibly pregnant women should consult a physician before using a Coast Freshe Cold Plunge Residential.

⚠ WARNING: The equipment and controls shall be located no less than 1.5 meters horizontally from the Coast Freshe Cold Plunge Residential.

⚠ CAUTION: Observe a reasonable time limit when using the Coast Freshe Cold Plunge Residential. Extended use increases the risk of hypothermia. Symptoms such as severe shivering, confusion, speech difficulties, loss of motor control, muscle rigidity, blue skin, or an irregular heartbeat.

⚠ CAUTION: Enter and exit the Coast Freshe Cold Plunge Residential slowly. Wet surfaces can be very slippery.

⚠ CAUTION: Proper chemical maintenance of the Coast Freshe Cold Plunge Residential water is necessary to maintain safe water and prevent possible damage to the components.

⚠ CAUTION: For use only within an enclosure rated CSA Enclosure 3.

⚠ CAUTION: The owner should test and reset the GFCI or RCD on a regular basis to verify its function.

⚠ WARNING: Maintain water chemistry in accordance with the Manufacturer's instructions.

⚠ CAUTION: Close the cover when not in use. This will help to discourage unsupervised children from entering the Coast Freshe Cold Plunge Residential. There is no representation that the cover, clip tie-downs, or actual locks will prevent access to the Coast Freshe Cold Plunge Residential.

⚠ CAUTION: Turn off the chiller immediately if the water is not flowing as it can cause ice to build up and damage the chiller unit.

⚠ CAUTION: To prevent damage to the chiller unit and plumbing system, drain and winterize the Coast Freshe Cold Plunge Residential if the ambient temperature drops to 36°F (2°C) or below, especially during winter.

Advisory: Any necessary repair must be carried out by a Coast Spas Authorized Service Provider. Coast Spas cannot accept liability for any damage resulting from alteration or repair performed by unauthorized technicians.

Advisory: Only professional or certified technicians should perform any work on the system.

⚠ WARNING: Keep access door always closed.

⚠ WARNING: Disconnect electric power before servicing.

⚠ WARNING: Shock hazard! No user serviceable parts inside.

⚠ WARNING: Do not attempt to service this control system. Contact your dealer or service provider for assistance.

⚠ WARNING: Follow instructions for all power connections as outlined in the owner's manual.

⚠ WARNING: Avoid swallowing water to prevent gastrointestinal illnesses or Legionnaires' disease from microbes like Cryptosporidium and Legionella.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

COAST FRESHE COLD PLUNGE RESIDENTIAL WHITE CHILLER BASIC OPERATION

CHILLER BASIC OPERATION

1. Fill the tub or system with water before connecting power.
2. Turn on the power at the main switch.
3. On the display:
 - Check that the current water temperature appears.
 - Use SET → UP/DOWN to choose your desired temperature (range: 3°C–45°C).
4. Press PUMP to start water circulation.
5. The chiller will automatically cool (or heat, if equipped) until the target temperature is reached.

CHILLER CONTROL PANEL INSTRUCTIONS

Important Notice: Upon initial receipt of the chiller after transport and whenever moving it without keeping the unit level upright or any time the unit has been tilted. Ensure the unit remains upright for a minimum of 6 – 12 hours before connecting it to power.

⚠ Caution: Do not turn the chiller upside down. Failure to follow this guideline may cause damage to the Coast Freshe Cold Plunge Residential.

Placing the Chiller and Ensuring Proper Ventilation

Chillers operate by transferring heat from one location to another. Specifically, a water chiller removes heat from the water and releases it into the surrounding air. To achieve this efficiently, adequate airflow is essential for optimal performance.

If the Coast Freshe Cold Plunge Residential is placed in a hot or poorly ventilated area, its ability to dissipate heat is significantly reduced, lowering its cooling effectiveness. Additionally, if the hot exhaust air from the chiller is recirculated back into its intake, the performance is compromised.

⚠ Caution: Close the cover when not in use. This will help to discourage unsupervised children from entering the Coast Freshe Cold Plunge Residential. There is no representation that the Coast Freshe Cold Plunge Residential cover will prevent access.

⚠ Caution: Keep air vents unobstructed and free from nearby objects. Routinely clean the vent screen to ensure proper ventilation and optimal system performance.

⚠ Caution: Do not connect the power unless the Coast Freshe Cold Plunge Residential is filled with water. Operating without water can cause damage to components and will void the warranty.

⚠ Caution: Adequate drainage and ventilation must be provided if the equipment is to be installed in a pit.

⚠ Warning: Water chiller is equipped with a GFCI plug, making it compatible with 110V - 120V 15A outlets the pre-installed cord is approximately 15 feet long. For optimal safety and performance, it is recommended to plug the chiller directly into a wall receptacle, avoiding the use of power strips.

⚠ Caution: If an extension cord is needed, it must be 12-gauge to provide sufficient power to the chiller and should not exceed 25 feet in length. Ensure that it is a 12 AWG cord with a single plug end (avoid multi-tap extensions).

⚠ Warning: After plugging in, verify that the GFCI is in the reset position to ensure proper functionality and safety. Please refer to the local electrical code requirements.

⚠ Warning: Ensure the power plug is firmly inserted into the socket outlet. Poor contact due to improper insertion may cause overheating and component failure, potentially leading to short circuits or a fire hazard.

⚠ Warning: Unplug during lightning storms or extended periods of non-use to prevent short circuits and reduce fire risk.

⚠ Warning: Do not handle the power plug or cord with wet hands to prevent the risk of electrical shock or serious injury.






CONTROL PANEL OVERVIEW: Front of Display



COAST FRESHE COLD PLUNGE

RESIDENTIAL





KEYS

Icon	Name	Description
<p>PUMP</p> 	WATER PUMP	Turn on or off the water pump.
<p>RUN</p> 	RUN	Run or stop the device only after the pump is running.
<p>UP</p> 	UP	In the case of parameter setting: Use to adjust parameters when the pump is not running: Press [UP] and [DOWN] or 5 seconds at the same time, the parameters are restored to factory defaults and the buzzer buzzes four times.
<p>SET</p> 	SET	If no parameter settings are displayed, press and hold down for 10 seconds to enter the distribution mode manually. The buzzer buzzes three times. In the case of parameter setting: Press to switch to parameter setting and hold down to exit parameter setting.
<p>DOWN</p> 	DOWN	In the case of parameter setting: Used to adjust parameters downward. When the pump is not running. Press [UP] and [DOWN] or 5 seconds at the same time, the parameter is restored to factory defaults and the buzzer buzzes four times.
<p>(S) ZONE</p>	OZONE	Turn the oxygen pump on or off.
<p>GH</p>	UV Light	Turn the lights on or off.

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL

LIGHT INDICATORS

Icon	Name	Description
	OZONE condition	Always bright: OZONE is on. Light off: OZONE is off
	UV Light condition	Always bright: Light is on. Light off: Light is off
	Defrosting condition	Always bright: Defrosting. Light off: Stop defrosting.
	Constant temp	Always bright: Target temperature reached. Light off: Not at target temperature.
	Alarm	Always bright: A fault occurs. Light off: No fault occurs.
	WiFi	Always bright: The server is connected. Blinking slowly: The server is not connected. Blinking rapidly: The network is being configured.


DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

COAST FRESHE COLD PLUNGE RESIDENTIAL WHITE CHILLER QUICK REFERENCE GUIDE



1. Carry handles: For carrying or moving the machine.
2. Control panel: For displaying the information and control the machine.
3. Power switch: For switching on/off the machine.
4. Metal cover/UV door: UV sterilizer inside the machine.
5. UV or Ozone sterilizer -Optional: inside the machine, for disinfection and sterilization of water.
6. Water strainer: To prevent the foreign things going into the water loop and damaging the machines.
7. Stand: For stabilizing the machine especially when it is working.
8. Cooling fan: For taking away the heat from the water.
9. Water hoses: For connecting and recirculating water between the machine and the bathtub or pool.
10. Power cord: For connecting the electric power from AC outlet.
11. Water outlet: For connecting the water hose to the inlet of bathtub or pool.
12. Water inlet: For connecting the water hose from outlet the bathtub or pool.
13. Drain-Optional: for drainage of wastewater in the machine, new version may not this drain.
14. Casters: For moving the machine, please lock it before turning it on.
15. Perforated air inlet: For getting the cool air into the machine.
16. RCD/GFCI: Leakage protection switch, for electrical safety, PLEASE TEST IT ONCE A WEEK AT LEAST, AND THE RCD PLUG IS NOT WATERPROOF.
17. Mounting bar on the bottom of machine-Optional: For mounting the machine on the wall by 4 sets of screws and 2 triangular wall racks just like the air conditioning mounting racks.
18. Mounting hole-Optional: for the external cartridge.

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL



1. ON/OFF button: Press and hold it for 2 seconds to start or stop the cooling system.
2. MODE button: Press and hold it for 5 seconds to exchange the temperature units °C and °F (new version).
3. SETTING button: Single click it for entering the temperature setting. Single click it for confirming and returning after the parameters setting.
4. W button: Press and hold it for 5-10 seconds to cancel and set up the APP connection.
5. UP button: Click or press and hold this touch button for increasing the setting values in setting mode.
6. DOWN button: Click or press and hold this touch button for reducing the setting values in setting mode. *Press and hold the UP button and DOWN button together for 5 seconds to lock or unlock the control panel.
7. SYSTEM information: For indicating the current working status of machine.
8. DEFROST information: For indicating the current working status of defrosting.
9. MODEL information: For indicating the mode of whole system under ICE BATH, AUTO or CONSTANT
10. WATER FLOW information: For indicating the water flow (new version only).
11. WIFI information: For indicating the connection status of WIFI.
12. WATER TEMPERATURE information: For indicating the current/real temperature of water from outlet of machine.
13. SETTING TARGET TEMPERATURE information: For indicating the setting temperature.
14. CHILD LOCK information: For indicating if the control panel is lock or not.

NOTE: TO SAVE ON YOUR ENERGY COST AND EXTEND PRODUCT LIFE, WE STRONGLY RECOMMEND THAT IT IS BEST TO SET THE TARGET TEMPERATURE TO BE NOT LESS THAN 5 DEGREES CELSIUS.


The real water temperature in the tub would be +1.5/-1 degrees Celsius different with the temperature shown on the screen because the water temperature sensor is not in the tub.

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026



UV and ozone working time setting.

The UV working time can't be adjusted. The ozone working time can be set. Refer to the following setting method:

Single click button 3 "F/S" --- Press and hold button 4 "C/W" for 5 seconds (or single click it) ---Click button 5 "UP" or 6 "DOWN" to adjust the ozone working time -----Single click button 3 "F/S" to confirm the setting - OK.

Normally, just keeping the ozone working time as short as possible, if not, the water may easy get oxidic and become yellow after treating by too much ozone if the quality of water is not so good.

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL WHITE CHILLER SMART CONTROL APP SET UP

Your Coast Freshe Cold Plunge Residential includes built-in Wi-Fi capability for remote monitoring and temperature control using the Smart Life mobile app (powered by Tuya Smart). Follow the steps below to connect your chiller to your smartphone.

1. Download the App


- You can download the Smart Life app for free:
- For iPhone (iOS): Visit the App Store and search “Smart Life.”
- For Android: Visit the Google Play Store and search “Smart Life.”
- Or scan the QR Code below:



Note: Make sure your phone is connected to a 2.4GHz Wi-Fi network (not 5GHz) during set up.

2. Create or Log into Your Account

1. Open the Smart Life app.
2. If you don't have an account, tap “Register” and follow the on-screen instructions.
3. You may also choose “Experience without Login” to try the app before registering.



1. Add a device
2. Enter Wi-Fi information.

3. Pairing Your Chiller


Before starting, ensure:

- The chiller is powered on.
- Your phone's Wi-Fi, Bluetooth, and Location (GPS) are all enabled.

Then follow these steps:

1. In the Smart Life app, tap the “+” icon in the top-right corner.
2. Select Add Device → Small Home Appliances → Temperature Controller (or similar).
3. The app will search for nearby compatible devices.
4. Once your chiller appears, tap Add.
5. Enter your Wi-Fi network name and password, then tap Next.
6. Wait while the app connects to the chiller (this may take up to 1 minute).
7. When the connection is successful, tap “Done” to complete set up.

Your chiller will now appear on the app's Home Page, allowing you to view and control settings remotely.



COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL BLACK CHILLER BASIC OPERATION

CHILLER CONTROL PANEL INTERFACE

HOME SCREEN DISPLAY

Current Measured Temperature

Up Button.
Press to increase the values.

Down Button.
Press to decrease the values.
- Short Press to turn screen backlight ON/OFF.

Setting Button.
- Short press to enter temperature setting.
- Long press to enter the internal parameter settings.

Emergency stop button.
- Short press to stop the compressor.
- Long press to use locking function.

**Note: After enter setting, it will automatically exit after a few seconds if no further action is taken.*

High Temp Alarm **Low Temp Alarm** **Lock** **Buzzer Indicator**

WIFI Indicator **Temperature Unit**











Cooling Mode Indicator **Compressor Indicator**
- Solid Lit: Compressor Is Working
- Flashing: Compressor Emergency Stop
- Not Lit: Compressor Stop Working

Start Temperature **Stop Temperature**

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.


COAST FRESHE COLD PLUNGE RESIDENTIAL

CHILLER CONTROL PANEL INSTRUCTIONS

1. Wipe the surface of the Coast Freshe Cold Plunge Residential before first use to remove dust and residue.
2. Insert the fill hose into the Coast Freshe Cold Plunge Residential and add water until it reaches the appropriate level. Fill with distilled or tap water, leaving 4-4.5 inches/11.00 centimeters from the top. If the water contains high mineral levels it is recommended to use a prefilter.
Note: Avoid over filling the Coast Freshe Cold Plunge Residential
3. Plug the power cord into an outlet to power up the Coast Freshe Cold Plunge Residential GFCI Box activate the water pump, allowing water to flow and circulate through the chiller system. If the pump makes a humming noise but no water movement, check the filter housing and strainer housing for airlock and follow the next step if needed.
4. Loosen the main filter housing and strainer housing to release any air lock, allowing water to fill the canister. Once the water reaches the top, tighten the housing back. If the canister is already filled with water, you can skip this step.
5. Remove the cap of the drain valve then open the drain valve to release any trapped air. Once the air is purged and the line is filled with water, close the valve and replace the cap.
6. Power on the chiller using the power switch. **Press**  as soon as the screen lights up to "Hold" the chiller compressor from starting before the settings are completed.
7. Short press  once, to enter the temperature setting. Once the "Start Temp" message begins to flash. Use  and  to adjust the temperature values.
8. Short press  once again, the "Stop temp" message will be flashing. Use  and  to adjust the temperature values.
9. Long press  to save and exit the temperature setting. Note: The chiller will not operate if the set temperature is higher than the current water temperature.
10. After 3 minutes, check the compressor indicator with the  symbol to confirm if it is solid or flashing. If it is flashing, short press the button  once to turn it on.
11. The compressor will activate, and the fan will start running. The chiller will gradually lower the water temperature to the set level.








Note: The compressor has a 3-minute delay after each start /reset cycle.

DISCLAIMER: The real water temperature in the tub would be +1.5/-1 degrees Celsius different from the temperature shown on the screen because the water temperature sensor is not in the tub.



COAST FRESHE COLD PLUNGE RESIDENTIAL

BUTTON OPERATION

Button Operation Instructions			
Interface	Main Screen Display	Set Start/Stop Temperature	Set System Parameters
Button			
	<p>Quickly press to enter the Start/Stop Temperature settings interface.</p> <p>Press and hold to enter the system parameter settings interface.</p>	<p>Quickly press to switch between the modified start and stop temperature values.</p> <p>Press and hold to save the value and exit.</p>	<p>Quickly press to toggle modified system parameters.</p> <p>Press and hold to save the value and exit.</p>
	<p>Short press: Not applicable.</p> <p>Long press: Not applicable.</p>	<p>Quickly press to increase the parameter value.</p> <p>Press and hold to quickly increase the parameter value.</p>	<p>Quickly press to increase the parameter value.</p> <p>Press and hold to quickly increase the parameter value.</p>
	<p>Quickly press to turn the screen backlight ON or OFF.</p> <p>Long press: Not applicable.</p>	<p>Quickly press to decrease the parameter value.</p> <p>Press and hold to quickly decrease the parameter value.</p>	<p>Quickly press to decrease the parameter value.</p> <p>Press and hold to quickly decrease the parameter value.</p>
	<p>Quickly press to toggle the emergency stop ON or OFF.</p> <p>Press and hold to enable or disable the button lock.</p>	<p>Short press: Not applicable.</p> <p>Long press: Not applicable.</p>	<p>Press quickly to toggle ON/OFF functions: OTP, LTP, dLy.</p> <p>Note: "--" indicates the function is turned OFF.</p> <p>Long press: Not applicable.</p>

NOTE: Please refrain from modifying any parameters other than the **start temp, stop temp, compressor emergency ON/OFF**. Improper adjustments may cause the chiller to malfunction.

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL BLACK CHILLER QUICK REFERENCE GUIDE



1. Carry handles: The Coast Freshe Cold Plunge Residential Chiller carry handle offers a sturdy, comfortable grip for effortless transport.
2. Control Panel: Displays information and enables easy operation of the Coast Freshe Cold Plunge Residential chiller.
3. Vents: Ensure proper airflow to maintain optimal operating temperatures for Coast Freshe Cold Plunge Residential equipment.
4. Rubber Stander: Stabilizes the Coast Freshe Cold Plunge Residential chiller and absorbs operational vibrations.
5. Cooling Fan: Ensures effective heat dissipation for optimal performance and longevity of the Coast Freshe Cold Plunge Residential chiller.
6. Power Cord: Connects the Coast Freshe Cold Plunge Residential chiller to an AC power outlet via the Coast Freshe Cold Plunge Residential GFCI box.
7. Water Outlet: Connects the water hose to the inlet of the Coast Freshe Cold Plunge Residential to return cooled water.
8. Water Inlet: Connects the water hose from the outlet of the Coast Freshe Cold Plunge Residential for cooling with the chiller.
9. Power Switch: Turns the Coast Freshe Cold Plunge Residential on and off.

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL BLACK CHILLER SMART CONTROL APP SET UP

Your Coast Freshe Cold Plunge Residential includes built-in Wi-Fi capability for remote monitoring and temperature control using the Sinilink mobile app. Follow the steps below to connect your chiller to your smartphone.

1. Download the App

- You can download the Sinilink app for free:
- For iPhone (iOS): Visit the App Store and search "Sinilink"
- For Android: Visit the Google Play Store and search "Sinilink"
- Or scan the QR Code below:



Once downloaded, install the app on your smartphone and register an account to proceed.



IMPORTANT: Ensure that your smart device is connected to Wi-Fi 2.4G only and that Bluetooth is enabled. Also, confirm that both your smart device and the Coast Freshe Cold Plunge Residential Chiller are within the same Wi-Fi 2.4G coverage area before proceeding with the app set up.

NOTE: Coast Freshe Cold Plunge Residential is not compatible with Wi-Fi 5G.




NOTE: When your smart device detects "Sinilink App" in Bluetooth search, **do not connect** to it directly. This Bluetooth connection must be made **within the app**.

If you have already paired it through your device's Bluetooth settings, please **cancel the pairing** and search again. Connecting outside the app may prevent successful pairing within the app.

2. Create or Log into Your Account


1. Open the Sinilink App and create an account.
2. Click "**Register**" under the **Login** tab.
3. Follow the on-screen instructions to complete the registration process.



3. Pairing Your Chiller

Click on "**Add a Device**" or tap the "+" symbol in the lower right corner.

NOTE: Ensure that your device is connected to your home Wi-Fi (2.4G only) before proceeding.




COAST FRESHE COLD PLUNGE RESIDENTIAL

4. Select **Compatibility Mode**.

Do not select **Touch Mode** or **Bluetooth Devices** during this step.




5. On this screen, **do not select anything**. Simply click **"Next"** at the bottom without making any changes.




COAST FRESHE COLD PLUNGE RESIDENTIAL

- 6. Tap to select the **checkmark**, which will highlight it. This action will change the "Next" button from **grey to orange**. Then, tap "Next" to proceed.




- 7. Select your **home Wi-Fi (2.4G only)** and enter your **Wi-Fi password**, then click "Next Step" to continue.





COAST FRESHE COLD PLUNGE RESIDENTIAL

- 8. Enter a custom name for your Coast Freshe Cold Plunge Residential. Next, tap the drop-down arrow to select the appropriate device classification.



- 9. Add a new classification; the name may be customized as needed.



COAST FRESHE COLD PLUNGE RESIDENTIAL

10. Copy the **password**, then go to your **smart device's Wi-Fi settings**.

NOTE: Do not press "Verify that the indicator flashes correctly."



11. Open your smart device's **Wi-Fi settings menu**, then go to the **Coast Freshe Cold Plunge Residential Chiller control panel** then press and hold the **up and down arrow buttons** for at least 5 seconds. You will see "SinilinkProduct" appear in the network selection.




COAST FRESHE COLD PLUNGE RESIDENTIAL

12. Select "**SinilinkProduct**" from the Wi-Fi network list. When prompted for a password, **paste the password** you copied from **Step 10 (12345678)**.




13. Once connected to the **SinilinkProduct** network, exit the **Wi-Fi settings** on your smart device and return to the **Sinilink app**. The connection should start **immediately**.



COAST FRESHE COLD PLUNGE RESIDENTIAL

14. Once you have successfully added your **Coast Freshe Cold Plunge Residential**, you will see the screen below. Select **"Back to Home Page"** to complete the set up.



15. Tap on the screen area where it says **"Control"** to access the device controls.



16. The **operation interface** of the app will now appear, giving you full control of your **Coast Freshe Cold Plunge Residential Chiller** from your smart device.



The cooling unit turns on when the current temperature is greater than or equal to the start temperature and turns off when the current temperature is less than or equal to the stop temperature. The Emergency Stop button is used to pause the Coast Freshe Cold Plunge Residential chiller.

NOTE: Please refrain from modifying any parameters other than the three with check mark above (start temp, stop temp, compressor emergency OFF). Improper adjustments of other values may cause the chiller to malfunction.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL CHILLER TROUBLESHOOTING GUIDE

If your chiller is not operating properly, follow the steps below to diagnose and resolve common issues. Regular maintenance and proper set up are essential to ensuring optimal performance.

ISSUE	POSSIBLE CAUSE	RECOMMENDED SOLUTION
Low Water Flow / Weak Discharge	<ul style="list-style-type: none"> • Pipe may be bent or kinked • Filter element may be clogged 	<ul style="list-style-type: none"> • Inspect all hoses for bends or blockages • Replace the filter element
Abnormal Compressor Noise or Vibration	<ul style="list-style-type: none"> • Incorrect input voltage • Poor ventilation • Water temperature exceeds 38°C • Ambient air temperature above 32°C • Fan malfunction or reduced airflow 	<ul style="list-style-type: none"> • Check and correct input voltage • Ensure chiller has proper ventilation • Lower water temp below 38°C • Improve ambient airflow • Verify fan is operating normally
Slow or Not Cooling	<ul style="list-style-type: none"> • Incorrect input voltage • Poor ventilation • Fan blowing hot air onto tub • Ambient air is too hot (>32°C) • Poor tub insulation or lid not used • Fan airflow significantly reduced 	<ul style="list-style-type: none"> • Confirm input voltage • Improve chiller ventilation • Redirect fan away from tub • Reduce surrounding air temperature • Use insulated lid properly • Check fan functionality
Display Screen Not Turning On	<ul style="list-style-type: none"> • Power cord not connected • Incorrect input voltage • SA30 controller cable loose 	<ul style="list-style-type: none"> • Ensure power is connected • Verify input voltage • Open unit and check TSC power cable
Abnormal Temperature Display	<ul style="list-style-type: none"> • External heat source near water line • Uneven water temperature • Poor contact on thermometer signal wire 	<ul style="list-style-type: none"> • Remove heat sources near pipe • Stir water to even out temperature • Check signal cable connection on TSC
Incorrect High/Low Temperature Alarm (Real Temp Between 1–42°C)	<ul style="list-style-type: none"> • App temperature alarm values incorrectly set • Thermometer error (see issue #5) 	<ul style="list-style-type: none"> • Adjust app alarm settings • Recheck temp sensor and connections
Circulation Pump Not Working	<ul style="list-style-type: none"> • No power to pump • Pump transformer not outputting 24V DC • Faulty pump 	<ul style="list-style-type: none"> • Test voltage at pump power source • Verify 24V DC output from transformer • Replace pump if both above • are normal
Screen is On, but Compressor and Fan Never Start (over 3mins)	<ul style="list-style-type: none"> • No voltage to chiller • Loose wire between TSC and compressor 	<ul style="list-style-type: none"> • Confirm chiller is receiving power • Open case and secure TSC wiring or compressor wiring

COAST FRESHE COLD PLUNGE

RESIDENTIAL

CHILLER NOT TURNING ON

- 1. Check Power Supply**
 - Ensure the chiller is plugged into a working outlet.
 - Verify the GFCI/GCD plug is not tripped.
- 2. Inspect Circuit Breaker**
 - If tripped, reset it and try again.

CHILLER NOT COOLING

- 1. Verify Controller Status**
 - Check if the LCD display has power.
 - Ensure the LED/Working Light symbol is lit on the controller.
 - If not, check the controller settings to confirm it is calling for cooling.
- 2. Compressor Functionality**
 - Ensure the compressor turns on and the controller readout remains steady.
- 3. Check Airflow**
 - Confirm airflow from the right side of the chiller is unobstructed.
 - Check for clogs in the coil or blockages in ventilation.
- 4. Assess Air Temperature**
 - If warm air is coming from the right side, the chiller is at least partially cooling.
 - If air is room temperature, further troubleshooting is needed.
- 5. Verify Water Temperature**
 - Use an external thermometer (not an IR gun) to check actual water temperature.
 - Compare readings from:
 - Ambient air temperature
 - Chiller display reading
 - External thermometer measurement
 - Clearly identifying temperature sources is crucial for accurate troubleshooting.
- 6. Ambient Temperature Consideration**
 - High room temperature can reduce cooling efficiency. Relocate the chiller to a cooler area if possible.

NO WATER FLOW BACK INTO TUB OR TANK

- 1. Check for Blockages**
 - Ensure the filter is clean and not restricting water flow.
 - If there is a valve on the tub drain, make sure it is fully open.
- 2. Perform Gravity Flow Test**

(Ensure the chiller is unplugged for at least 30 minutes before performing this test.)

 - Remove the filter from its housing and reattach the housing without the filter.
 - Disconnect the inlet fitting – verify strong gravity-fed water flow. Reconnect the fitting.
 - Disconnect the outlet fitting – ensure good gravity flow before reconnecting.
 - Disconnect the filter connection fitting, lower the tubing, and check for water flow.
 - Plug the chiller back in, observe water flow increase, and reconnect the fitting.
- 3. Backflush the System (If water flow issues persist)**
 - Remove the tubing from the outlet of the chiller.
 - Use a garden hose to flush the system backwards through the outlet.
 - Continue flushing for 15-30 seconds until air bubbles stop appearing in the tub.
 - Reconnect the tubing, turn on the chiller, and check for restored water flow.
- 4. Identify Flow Obstructions**
 - If water is not flowing at any step, determine where the blockage occurs (inlet, outlet, filter hose, etc).

COAST FRESHE COLD PLUNGE RESIDENTIAL

PUMP CIRCULATION ISSUES

1. Check Hose Connection

- Ensure the hose from the ice bath is securely attached to the pump.
- Look for kinks, loose connections, or blockages restricting flow.

2. Ensure Proper Positioning

- The water level in the ice bath should be higher than the chiller's inlet.
- This allows gravity to assist water flow and prevent air pockets.

3. Prime the Pump

- If the pump is not pulling water, disconnect it, fill it with water, then reconnect.
- This removes trapped air and restores proper function.

4. Restart the System

- Turn off the chiller and pump, wait a few minutes, then restart them.
- This can help reset internal components and clear minor issues.

5. Inspect for Obstructions

- Check the pump's intake for debris or clogs hindering flow.
- Ensure the filter assembly is clean and free of air pockets.

6. Still Not Working?

- If circulation issues persist, contact your seller for assistance.
- Provide a video of your set up and describe the issue in detail.

OTHER COMMON ISSUES

1. Unusual Noises

- Check for obstructions in vents and fans.
- Secure loose components to prevent rattling.

2. Water Leakage

- Ensure all hoses and fittings are securely connected.
- Inspect for cracks or damage causing leaks.

3. Error Messages on Display

- Refer to the user manual for specific error codes.
- Reset the chiller by turning it off, waiting a few minutes, and restarting.

4. Chiller Overheating

- Ensure proper ventilation and avoid placing the chiller in a confined space.
- Monitor ambient temperature, as excessive heat can cause overheating.

DISCLAIMER: Please check your unit to determine whether it is equipped with a black or white chiller. Follow the instructions specific to the chiller installed in your unit.

COAST FRESHE COLD PLUNGE RESIDENTIAL


GLOSSARY OF TERMS



CHILLER: A water chiller for an ice bath is a device designed to efficiently cool water to a low temperature. It is commonly used in sports recovery, physical therapy, and other applications where cold-water therapy is beneficial. These chillers provide a safe and effective ice bath experience by maintaining a consistent and controlled water temperature. This eliminates the need to constantly replenish ice, making it a convenient and cost-effective solution for athletes, coaches, and healthcare professionals incorporating cold water therapy into their treatment or training routines.



SKIMMER: This is the rectangular outlet at the water level. The skimmer removes surface debris to the filter. The water level in the unit should be kept $\frac{1}{2}$ to $\frac{3}{4}$ up on the skimmer for optimum operation.



SUCTION: During operation of the equipment, the suction works in conjunction with the skimmer to draw water from the bottom of the unit through the filter, keeping the unit sparkling clean.



SAND FILTER: The Sand Filter is designed to remove impurities and debris from water by filtering it through layers of sand. It captures particles such as dirt, algae, and organic matter, helping to maintain water clarity and hygiene.



BALL VALVE: A ball valve is a type of shut-off valve that controls the flow of water through the plumbing using a rotating ball with a hole (bore) through its center.

PREPARATION, SET-UP AND LOCATION FOR YOUR NEW COAST FRESHE COLD PLUNGE RESIDENTIAL:

For spas or hot tubs installed indoors, care should be taken to ensure adequate ventilation for the indoor space to avoid undesired buildup of humidity due to spa water. For additional information on ventilation and humidity guidelines, see the ASHRAE Handbook – HVAC Applications, I-P Edition, Sections 4.5, 4.6, and 4.7.

- You want to keep in mind how you intend to use the unit and plan the location accordingly.
- How close is the unit from the exit or entrance to your house? (consider the cold weather)
- Is the path to your unit clean of debris, sand, grass? (so as not to track into the unit).
- Is there protection from wind, inclement weather?
- Can neighbors or passersby see the unit?


NOTE: Allow for service access: Many owners enjoy placing their unit in a decorative enclosure or a deck. Keep in mind that you need to have access to the equipment for maintenance and the unit should be able to be moved or lifted without destroying the special enclosure or its surroundings. You should discuss this with your dealer when designing the location. Extension cords are not to be used in conjunction with the operations of the unit. Low voltage damage could result, and this is not covered by warranty.

DISCLAIMER: The pictures displayed above are for reference purpose only. Some parts may be different depending upon the unit model.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL GENERAL LAYOUT

(Your Coast Freshe Cold Plunge Residential may look different)



DISCLAIMER: The pictures displayed above are for reference purpose only. Some parts may be different depending upon the unit model.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL SPECIFICATION



Specification	Coast Freshe Cold Plunge Residential
Dims (cms)	211 x 84 x 76 cm
Dims (in)	83" x 33" x 30"
Capacity (L)	340 L
Capacity (US gal)	90 gal
Dry Wt (kg)	121 kg
Dry Wt (lbs)	265 lbs
Wet Wt (kg)	461 kg
Wet Wt (lbs)	1015 lbs
Electrical (V)	110 V

DISCLAIMER: At the time of print, this manual is accurate in its information. Coast Spas reserves the rights to change or modify any unit designs and/or features without notification. To check on updates or for other information, please visit www.coastspas.com

COAST FRESHE COLD PLUNGE RESIDENTIAL CARE GUIDE

Your authorized dealer carries a wide variety of care and maintenance products. For more information, please contact your Dealer.

SAND FILTER MAINTENANCE & REPLACEMENT

The sand filter system ensures crystal-clear water by trapping debris in a bed of No. 20-40 standard silica sand (particle size: 0.45–0.55 mm). Proper maintenance and periodic sand replacement are essential for optimal performance.

Routine Maintenance

Monitor Filter Pressure

- Record the clean filter pressure at initial start-up.
- When pressure rises 5–10 psi above the clean reading, backwash the filter.

Backwash Indicators

- Flow reduction by 30% from original clean flow.
- Pressure gauge increase of 10 psi over clean reading.
- Visible reduction in water flow from return jets.

Backwash Procedure

Multiport Valve Positions

1. Turn pump OFF before changing valve positions.
2. Set valve to BACKWASH; open suction and waste lines.
3. Start pump; backwash for 3–5 minutes or until water runs clear.
4. Stop pump; set valve to RINSE; run for 30 seconds.
5. Stop pump; set valve to FILTER; restart pump for normal operation.

Note: If pressure remains 4–6 psi higher after backwashing, perform a chemical cleaning of the sand bed.

CHANGING SAND FILTER

Filter Tank & Standpipe Assembly

Replace sand every 3–5 years or sooner if water clarity issues persist.

Steps:

1. Turn off power and drain the filter tank completely.
2. Remove the multiport valve and standpipe assembly.
3. Scoop out old sand and dispose of it safely.
4. Inspect and clean the underdrain assembly.
5. Add water to half-fill the tank (to cushion sand addition).
6. Pour in the correct amount of No. 20-40 silica sand.
7. Reinstall the standpipe and valve, ensuring proper alignment.
8. Tighten the clamp securely and check for leaks.



CHEMICALS (USA)

Coast Spas chemicals play a vital role in ensuring the longevity, cleanliness, and overall enjoyment of your hot tub, swim spa or cold plunge experience.

For optimal performance and to ensure the longevity of your Coast Spas hot tub, swim spa & cold plunge, we strongly recommend using Coast Spas chemicals. Our specially formulated chemicals have been crafted with the utmost precision and care, utilizing premium-grade ingredients and formulations designed to complement the unique engineering of your Coast Spas hot tub, swim spas & cold plunge.

The use of alternative chemical products may lead to unintended chemical reactions, water imbalance, and possible damage to your spa's components. It is important to note that failure to use Coast Spas chemicals may impact your warranty coverage. To safeguard your investment and enjoy uninterrupted relaxation, trust in the quality and compatibility of Coast Spas chemicals — the ideal choice for your Coast Spas hot tub, swim spas & cold plunge.

SCAN THIS QR
TO DOWNLOAD
BROCHURE



Coast Spas®

HIGH QUALITY FORMULATION

Coast Spas chemicals are designed to be easy to use and require minimal effort to maintain. This means that customers can spend less time worrying about maintaining their hot tubs, swim spas & cold plunge and more time enjoying them.

EASY TO USE

Coast Spas chemicals are safe and effective, providing superior user experience for customers. They are designed to work seamlessly with Coast Spas hot tubs, swim spas & cold plunge, ensuring that customers can enjoy their hot tubs, swim spa & cold plunge without any issues.

RELIABLE AND EFFICIENT

Coast Spas chemicals are safe and effective, providing a superior user experience for customers. They are designed to work seamlessly with Coast Spas hot tubs, swim spa & cold plunge, ensuring that customers can enjoy their hot tubs, swim spa & cold plunge without any issues.





CHEMICALS (CANADA)

Coast Spas chemicals play a vital role in ensuring the longevity, cleanliness, and overall enjoyment of your hot tub, swim spa & cold plunge experience.

For optimal performance and to ensure the longevity of your Coast Spas hot tub, swim spa & cold plunge, we strongly recommend using Coast Spas chemicals. Our specially formulated chemicals have been crafted with the utmost precision and care, utilizing premium-grade ingredients and formulations designed to complement the unique engineering of your Coast Spas products.

The use of alternative chemical products may lead to unintended chemical reactions, water imbalance, and possible damage to your spa's components. Moreover, it is important to note that failure to use Coast Spas chemicals may impact your warranty coverage. To safeguard your investment and enjoy uninterrupted relaxation, trust in the quality and compatibility of Coast Spas chemicals – the ideal choice for your Coast Spas hot tub, swim spa & cold plunge.

**SCAN THIS QR TO
DOWNLOAD
BROCHURE**



HIGH QUALITY FORMULATION

Coast Spas hot tub, swim spa & cold plunge chemicals are designed by a team of experienced chemists who understand the unique needs of hot tubs, swim spa & cold plunge. They are formulated to provide optimal performance and reliability in Coast Spas hot tubs, swim spas & cold plunge ensuring that customers can enjoy their hot tubs, swim spas & cold plunge for longer periods of time.

EASY TO USE

Coast Spas chemicals are designed to be easy to use and require minimal effort to maintain. This means that customers can spend less time worrying about maintaining their hot tubs, swim spa & cold plunge and more time enjoying them.

RELIABLE AND EFFICIENT

Coast Spas chemicals are safe and effective, providing a superior user experience for customers. They are designed to work seamlessly with Coast Spas hot tubs, swim spa & cold plunge, ensuring that customers can enjoy their hot tubs, swim spa & cold plunge without any issues.

COAST FRESHE COLD PLUNGE RESIDENTIAL

CHEMICAL HANDLING SAFETY

Proper handling of chemicals is essential to ensure safe operation and protect users from injury. Always follow Manufacturer's instructions and established safety standards when storing, mixing, or applying chemicals.

General Safety Guidelines

Personal Protective Equipment (PPE)

To ensure safety when handling chemicals:

- Always wear gloves and goggles.
- Avoid inhaling fumes. Use chemicals in a well-ventilated area.
- Avoid contact with skin, eyes, and clothing.
- Wash hands thoroughly after handling chemicals.

Mixing and Use Precautions

- **⚠ Never mix chlorine and acid.** This combination can create toxic gases that can cause severe injury or death.
- Always add chemicals to water, never water to chemicals.
- Use only Coast Spas approved sanitizers and water treatments.
- Carefully follow the dosage and application instructions provided by the chemical manufacturer.
- Do not use household cleaning agents in your unit.

Storage and Handling

- Store chemicals in their original containers with labels intact.
- Keep containers tightly closed when not in use.
- Store in a cool, dry, and well-ventilated area, away from direct sunlight and heat sources.
- Keep out of reach of children and pets.
- Store oxidizers and acids separately to prevent chemical reactions.

Spill and Exposure Response

- In the event of a chemical spill, clean immediately using non-reactive tools.
- Dispose of materials safely, according to local regulations.
- If chemicals contact skin or eyes, rinse immediately with clean water for at least 15 minutes and seek medical attention if irritation persists.
- If chemical fumes are inhaled, move to fresh air immediately and seek medical attention.

Regulatory Compliance

All chemical handling, storage, and disposal must comply with the following safety systems and standards:

- [WHMIS](#) (Canada)
- [OSHA](#) (USA)
- SDS/MSDS: Always refer to the Safety Data Sheet for each chemical used. This contains detailed instructions on hazards, handling, storage, and first aid.

COAST FRESHE COLD PLUNGE

RESIDENTIAL

OWNER'S MANUAL

2026

COAST FRESHE COLD PLUNGE RESIDENTIAL

CHEMICAL SAFETY GUIDELINES

Before installing or operating your Coast Freshe Cold Plunge Residential, carefully review all chemical safety instructions, operational precautions, and warranty information to ensure safe and proper use.

Chemical Safety

Muriatic Acid & Liquid Chlorine Information

The following chemicals are recommended for use with the Coast Freshe Cold Plunge Residential:

- Muriatic Acid (14.5% Hydrochloric Acid)
- Liquid Pool Chlorine (10% Sodium Hypochlorite)

Refer to the Safety Data Sheets (SDS) for detailed handling instructions:

- [HDX Muriatic Acid SDS](#)
- [Acid Blue Muriatic Acid SDS](#)
- [HDX Liquid Pool Chlorine SDS](#)


Water Chemistry Guidelines

- Always review chemical handling instructions, SDS documents, and warning labels on chemical reservoirs before adding any chemicals.
- For the Auto Doser system:
 - Chlorine: Use Liquid Chlorine (10–12.5% Sodium Hypochlorite)
 - pH Down: Use Swimming Pool Muriatic Acid Balancer (14.5% Hydrochloric Acid)
- Add only the correct chemical to its designated reservoir. Never mix chemicals or add powdered/diluted chemicals.
- Use only recommended chemicals. Substitutions or higher concentrations may damage the system and void the warranty.
- After set up, allow the Auto Doser to cycle for 24 hours before use to stabilize water chemistry.
- Encourage all users to shower prior to use to maintain proper water balance.
- Outdoor use may reduce chemical lifespan due to UV exposure and environmental debris.
- Do not use untreated well water. If on well water, properly filter it using an ion exchange system before filling the plunge.
- The system is calibrated for cold water only; do not exceed recommended water parameters.

Auto Doser Probe Instructions

- The probe ships in a wet storage solution. Ensure it does not dry for more than 15 minutes, or readings may fail.
- If storing the plunge, remove the probe and return it to its storage cap with solution. Contact technicalsupport@coastspas.com for guidance.
- The silver probe wrench included in the Auto Doser Starter Kit is used to install and remove the probe.

Auto Doser Controller Overview



- pH Reading: Maintains ~7.35 pH (acceptable range 7.1–7.5). To raise pH, use a recommended pH increaser. Always test water before adding chemicals.
- ORP Reading: Measures the water's ability to sanitize itself. Target ~735 mV (range 690–875 mV).
- Water Temperature: Displays the current water temperature in °F.
- Status Light: Blinks yellow/red if probe readings are outside the acceptable range. Press Help for details.
- Service Light: Blinks yellow/red when maintenance is required. Press Help for instructions.
- Help Button: Shows active error codes and guidance.
- Menu Button: Access set up mode, manual pump controls, and pH/ORP/temperature settings.
- Arrow & Selection Buttons: Navigate the menu and adjust settings.
- Silver Connection Port: Connects the Auto Doser probe.
- Peristaltic Tubing: Transfers chemicals from reservoirs into the plunge.
- Power Rocker Switch: Turns the Auto Doser controller on/off.

COAST FRESHE COLD PLUNGE RESIDENTIAL

Warranty & Maintenance

- Damage caused by freezing temperatures or improper water chemistry is not covered under warranty.
- Monitor your Coast Freshe Cold Plunge Residential closely when temperatures approach 32°F / 0°C. If ambient temperatures stay below freezing for 12 hours, drain and winterize the plunge, filter, and chiller.
- The Coast Freshe Cold Plunge Residential should operate continuously (24/7). Stagnant water can cause unsanitary conditions and buildup inside pipes. Follow the cleaning and maintenance protocols in this manual.
- Extension cords: Use a 12-gauge cord (up to 25 feet) if needed and follow local electrical codes. Outdoor cords must be protected with a weatherproof connection box.
- For additional support, contact technicalsupport@coastspas.com or submit a ticket through our website: www.coastspas.com.

IMPORTANT NOTICE

- Flooring: Ensure the installation surface is waterproof/resistant to prevent damage.
- Power: Do not energize the system until the plunge is filled to the required level. Running the pump dry can cause immediate damage and void the warranty.
- Deck Installation: Confirm that your deck can safely support the filled plunge. Consult a qualified contractor or structural engineer. The filled plunge weighs 1015 lbs / 461 kg.
- Water Chemistry: Follow the manual's water chemistry guidelines. Improper chemical balance can damage the system or cause skin irritation.

COVER CARE

A well cared for unit cover is a thing of beauty in its own right. Be sure to clean and condition your cover at least once a month (more often if needed).

WEATHERSHIELD COVER MAINTENANCE PROCEDURE

Weathershield is a solution dyed polyester fabric designed to be flexible and easy for manufacturers to use. Its urethane coating enhances the stability of the weaves and allows for greater water resistance, while also minimizing shrinkage and stretching.

Weathershield features a high UV, water and mold and mildew resistance and have excellent tear and abrasion resistance.

CARE & CLEANING

Weathershield is designed to be easy to maintain. It can be washed or brushed off and rinsed. Proper care and cleaning are important to the life of all fabrics.

FOR NORMAL CARE AND CLEANING

- Add 2 ounces of mild soap such as Woolite or Dawn dishwashing liquid to 1 gallon of lukewarm water.
- Clean the fabric with a "soft bristle brush". Rinse thoroughly with cold water and air dry.

FOR STUBBORN STAINS

- Add maximum 1 cup of bleach to one 1 gallon of water.
- Spray on lightly to the fabric face (non-coated side). Do not soak fabric.
- Prolonged exposure to harsh chemicals can damage the coating.
- Rinse immediately. Do not leave on for more than 2 minutes.

Cleaning with harsh cleaners such as bleach will require re-treatment like 303 High Tech Fabric Guard for restoring water repellency.

⚠ Important Notice: DO NOT leave your unit drained and in direct sunlight for extended periods of time. Extreme heat could cause damage to the acrylic surface and may induce an effect known as "crazing". Crazing is not covered under spa limited warranty.

COAST FRESHE COLD PLUNGE RESIDENTIAL

Public Health & Infection Control

Proper Coast Freshe Cold Plunge Residential maintenance is essential to protect user health and prevent bacterial growth, including Legionella, Pseudomonas, and other harmful microorganisms. Failure to maintain clean, disinfected water can lead to serious illnesses such as Legionnaires' disease, folliculitis, ear or skin infections.

⚠️ Key Health Risks

- Legionella bacteria can grow in warm water and aerosols, potentially causing Legionnaires' disease. ([CDC](#))
- Pseudomonas and other microorganisms can form biofilm in pipes and spa surfaces, causing skin, ear, or respiratory infections. ([CDC](#))
- Even clear water can harbor bacteria if not properly sanitized. ([Health Canada](#))

To minimize health risks:

- Sanitize water daily and maintain correct pH:
 - Free chlorine ≥ 3 ppm
 - Bromine ≥ 4 ppm
- Disinfect and shock-treat the water regularly following chemical Manufacturer's instructions.
- Drain, clean, and scrub the unit and components to remove biofilm and sediment.
- Clean and replace filters according to the maintenance schedule.
- Keep accurate water-testing logs, especially for commercial or multi-user units.
- Follow chemical dosing instructions carefully and maintain water balance daily.

⚠️ Important Notice: Failure to maintain proper sanitation, chemical balance, and cleaning routines can create serious health risks and may void your warranty. Always follow the instructions in this manual and those from chemical suppliers.

For more information, refer to:

Health Canada: [Guidelines for Canadian Recreational Water Quality – Public Spa Pools](#)

Centers for Disease Control and Prevention (CDC): [Preventing Legionella in Hot Tubs and Spas](#)

Safety Signage for Coast Freshe Cold Plunge Residential

For user safety, Coast Spas recommends placing a caution sign near the cold plunge:



⚠️ CAUTION: Cold water immersion can cause cardiac stress. Exit immediately if you experience dizziness, shivering, or numbness.

This sign is intended to alert all users to potential risks and promote safe operation of the Coast Freshe Cold Plunge Residential.

Skimmer Instructions

1. Use a clean skimming net to remove floating debris such as leaves, hair, or insects from the water surface.
2. Sweep the bottom of the tub to collect any settled particles.
3. Skim the water at least once per week, and ideally before each use.
4. For outdoor installations, skim more frequently during windy conditions or when nearby plants are shedding.
5. Always rinse the skimmer net after use and store it in a clean, dry location.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

COAST FRESHE COLD PLUNGE RESIDENTIAL SET UP GUIDE

Step 1: Choosing a Safe Location

⚠ WARNING: Risk of Electric Shock.

Install your Coast Freshe Cold Plunge Residential at least 1.5 meters (5 feet) away from electrical outlets, appliances, or other sources of electricity.

Placement Guidelines:

- Set the plunge on a solid, level, and waterproof surface.
- Ensure at least 16 inches of clearance along the side housing components for proper ventilation.
- Maintain a minimum of 24 inches of space on the equipment side for maintenance access.


Step 2: Filling the Plunge

- Connect a water filter to a garden hose.
- Run water through the filter and into a drain until it runs clear of debris.
- Fill the Coast Freshe Cold Plunge Residential with filtered water.
- Water should reach halfway up the skimmer to ensure proper circulation.

Step 3: Installing the Probe

- The probe cap contains a saline solution to keep it moist. Hold the probe vertically with the cap down when removing it to prevent spills.
- Some salt residue on the cap is normal. If the inside of the cap is dry, the probe may require recalibration.
- Keep the cap safe for future storage; the solution does not need to be saved.
- Insert the probe into the marked location and secure it with the provided silver probe wrench.
- Open the two-colored ball valves (turn handles parallel to the tubing). Ensure the white drain valve remains closed and capped.
- Check the probe wire is untwisted and connect the silver probe connector to the Auto Doser's bottom-right port. Hand-tighten the collar to secure.

⚠ Important: The probe must not be left dry for more than 15 minutes to avoid damage.



Step 4: Adding Chemicals to the Auto Doser


- Each reservoir is labeled for a specific chemical. Only add the correct chemical to the corresponding reservoir. Do not mix chemicals.
- Remove the caps and locate the MIN and MAX fill lines.
- For the initial fill, add chemical just above the MIN line.
- Replace and tighten caps securely.
- After the Coast Freshe Cold Plunge Residential has run for 24 hours, fill each reservoir up to the MAX line.

Recommended Chemicals:

- Swimming Pool Muriatic Acid Balancer (14.5% Hydrochloric Acid)
- Liquid Chlorine (10–12.5% Sodium Hypochlorite)

⚠ Safety Notice: Always read the Chemical Safety Data Sheets (SDS) and follow proper handling instructions before adding chemicals.

COAST FRESHE COLD PLUNGE RESIDENTIAL



Step 8: Water Maintenance

- Balance the water before allowing any use. Proper chemical balance ensures safety and prolongs equipment life.
- Test and adjust water chemistry according to instructions.

⚠ Do not skip water testing and balancing.

Unbalanced water can damage the system and void the warranty.

Proper maintenance extends the life and functionality of the Coast Freshe Cold Plunge Residential. Not following the maintenance instructions will void the warranty. For any questions, please email us at

technicalsupport@coastspas.com

Step 5: Connecting to Power

- Allow the Coast Freshe Cold Plunge Residential to rest for at least 20 minutes after moving to let the coolant settle.
- Plug the unit into a dedicated 120V, 15A circuit. Do not use a circuit shared with other appliances.
- Ensure the outlet is at least 5 feet away from any body of water.

Step 6: Powering On the Coast Freshe Cold Plunge Residential

- Locate the “Test” and “Reset” buttons on the power cord.
- Press “Reset” to turn on the Cold Plunge.
- The jets should activate, and the LED display on the chiller will show the current water temperature.

Step 7: Setting the Temperature

- Use the chiller’s controls to select your desired water temperature.

COAST FRESHE COLD PLUNGE RESIDENTIAL

COAST FRESHE COLD PLUNGE RESIDENTIAL WATER CARE GUIDE

We're thrilled you're enjoying your Coast Freshe Cold Plunge Residential! Proper care keeps your plunge operating efficiently, water clean and safe, and ensures your warranty remains valid. Regular maintenance also extends the life of your unit and helps avoid costly repairs.

Note: These are minimum recommended intervals. Units with high usage (more than 20 plunges per day) may require more frequent maintenance.

IMPORTANT: The spa or swim spa water shall be tested and treated in accordance with applicable local codes. For Pool and Hot Tub Water Sanitation, see [Uniform Swimming Pool, Spa and Hot Tub Code](#), Chapter 5 – Water Quality.

Daily Care

- Skim the water to remove leaves, hair, or debris.
- Clear debris from drain strainers.
- Wipe the waterline to remove any surface film or buildup.
- Test water chemistry daily and adjust as needed using the Coast Freshe Cold Plunge Residential Water Maintenance Protocol.

Every Two Days – Skimmer Maintenance

Cleaning Your Skimmer:

1. Open the skimmer housing by gently pulling it forward.
2. Remove the basket and empty all debris. Rinse thoroughly under running water.
3. Replace the basket and close the skimmer housing.

Tip: Keeping the skimmer clean ensures proper water circulation and helps maintain optimal water quality.

Weekly – Sand Filter Maintenance

Replacing the Filter:

1. Backwash the filter when the pressure gauge reads 5–10 psi above the clean level.
2. Turn off the pump, set the valve to BACKWASH, and run for 3–5 minutes until water runs clear.
3. Switch to RINSE for 30 seconds, then return to FILTER.
4. Inspect hoses and connections for leaks and ensure proper water flow.

5. Verify the o-ring is seated and free of debris before replacing the cover. Hand-tightening only; over-tightening can damage threads.

Tip: A clean filter keeps water flowing efficiently and protects the system from damage.

Every Four Weeks – Water Replacement & Drain Strainers

Draining and Refilling:

1. Pause the plunge and wait for jets to stop.
2. Turn off the unit completely (unplug or press the “test” button).
3. Remove the ventilation screen opposite the filter housing.
4. Remove the spigot cap and attach a garden hose to drain water. Drain speed may vary with hose length and elevation.
5. Replace the cap after draining.

Cleaning Drain Strainers:

6. Drain the plunge completely.
7. Remove each strainer by unscrewing the small notches.
8. Clean thoroughly with a brush and use a pin to remove any stuck debris.
9. Reinstall the strainers, refill the plunge, and power it on.

Tip: Replacing water regularly keeps it clean, safe, and prevents long-term system wear.

Every Three Months – Ventilation Screen Maintenance

Cleaning the Screens:

1. Remove the ventilation screen by lifting from the bottom.
2. Rinse under running water to remove dust and debris.
3. Shake off excess water and allow to air dry briefly.
4. Reinstall the screen by inserting the top lip first and pressing gently into place.

Tip: Clean screens maintain proper airflow and reduce dust accumulation in the system.

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

Every Six Months- Deep Cleaning

Items Needed: Household degreaser, sponge or cloth, jet cleaner, sanitizer, new filter

Step 1 – Jet Cleaning:

1. Turn off and drain the plunge completely.
2. Wipe down all surfaces with degreaser, then rinse thoroughly.
3. Refill the plunge with water 2 inches above the highest jet or drain. Add warm water if needed.
4. Replace the filter if it is 3–4 weeks old or visibly dirty.
5. Add the recommended jet cleaner to the water and run the system for 15 minutes at maximum temperature.
6. Pause the system for 1 hour, then run again for 15 minutes.
7. Drain and rinse the plunge thoroughly.

Step 2 – Sanitizing:

8. Refill the plunge to 2 inches above the highest jet or drain.
9. Turn the jets on and set the temperature to maximum.
10. Add the recommended sanitizer (do not mix different types).
11. Run the plunge for 20 minutes, then continue filling to full capacity while running.

Tip: A deep clean every six months removes buildup, protects the system, and keeps water safe for regular use.

Coast Freshe Cold Plunge Residential Water Maintenance

To keep your Coast Freshe Cold Plunge Residential water safe and clean, see below for a protocol we recommend. This is a protocol that we've seen work well for most situations. Please keep in mind that water chemistry can be different based on the quality of your water in your jurisdiction.

If you are on well water, please make sure you have the ability to properly reduce calcium levels before filling the tub. High amounts of calcium can damage the pump over time.

Poor water quality can lead to skin infections, ear infections, and urinary tract infections. That's why it's important to monitor and manage the quality of the water routinely.

These water maintenance instructions are meant to be used alongside the regular maintenance protocols for your Coast Freshe Cold Plunge Residential. For more guidance, please email technicalsupport@coastspas.com.

Residential Chlorine Water Maintenance Manual

To keep your Coast Freshe Cold Plunge Residential water safe and clean in a residential environment, see below for a protocol we recommend. This is a protocol that we've seen work well for most situations. Please keep in mind that water chemistry can be different based on the quality of your water in your county. If you are on well water, please make sure you have the ability to properly reduce calcium levels before filling the tub. High amounts of calcium can damage the pump over time. These water maintenance instructions are meant to be used alongside the regular maintenance protocols for your Coast Freshe Cold Plunge Residential.

Products needed:

Coast Spas Chemical Starter Kit Includes:

- Alkalinity Booster (100 g)
- Calcium Booster (100 g)
- Chlorine (100 g)
- pH down (100 g)
- pH Up (100 g)
- Stain & Scale (500 mL)
- Testing Kit

⚠ Important: Wait 15 minutes between adding different chemicals. This helps them mix properly.

Follow these steps each time you drain and refill your plunge:

- Fill your Coast Freshe Cold Plunge Residential with clean, fresh water.
- Test the water with your chlorine test strips to check alkalinity and pH.
- Adjust alkalinity first, then pH, following the guidelines in the tables provided.

COAST FRESHE COLD PLUNGE

OWNER'S MANUAL

RESIDENTIAL

2026

Daily Water Care

Maintenance may need to be done more often if the plunge is heavily used.

1. Check the water daily using your chemical testing kit and adjust as needed.
2. Wipe the waterline with a sponge to remove any buildup.
3. Clean the drain strainers by removing hair or debris to keep water flowing smoothly.

Tip: Always wait at least 15 minutes between adding each chemical.

Chlorine Table

Please wait 1 hour before retesting and adding more chemicals.

Chlorine Reading	Add
0 - 1 PPM	2 Teaspoons of Replenish
2 PPM	1 Teaspoon of Replenish
3 - 5 PPM	Leave as is
Over 5 PPM	Add fresh water to the Plunge

Alkalinity Table

Please wait 1 hour before retesting and adding more chemicals.

Alkalinity Reading	Add
0 - 20	4 Tablespoons of Spa Up
21 - 40	3 Tablespoons of Spa Up
41 - 60	4 Teaspoons of Spa Up
61 - 80	1 Teaspoon of Spa Up
81 - 120	Leave as is
Above 120	Add 1 Tablespoon of Spa Down and let the water cycle for 1 hour. If it's still high, repeat.

We recommend adjusting and stabilizing Alkalinity first and then pH.

pH Table

Please wait 1 hour before retesting and adding more chemicals.

pH Reading	Add
Below 7.0	1 Tablespoon of Spa Up
7.0 - 7.1	2 Teaspoons of Spa Up
7.2 - 7.8	Leave as is
7.9 or above	Add 1 Tablespoon of Spa Down and let the water cycle for 1 hour. If it's still high, repeat.

Residential Non-Chlorine Water Maintenance

To keep your Coast Freshe Cold Plunge Residential water safe, clean, and refreshing in a residential setting, follow the protocol below. This non-chlorine care routine has proven effective when performed consistently. However, chlorine-based systems can also be used if they better suit your facility's needs. If the water becomes cloudy or develops an odor, it's best to drain and refill the plunge with fresh water. If the plunge ever stops filtering or is turned off, be sure to empty the plunge, the filter, and the chiller. Still water can become unsanitary and may affect performance.

⚠ Important: If water is not circulating, turn off the chiller immediately to prevent damage.

Key: Tbsp = Tablespoon | Tsp = Teaspoon

Initial Set up (After Each Drain and Refill)

Coast Freshe Cold Plunge Residential:

1. Fill the plunge with clean, fresh water using a carbon hose filter if available.
2. Add 3 tablespoons of Coast Spas Alkalinity Booster to balance alkalinity.
3. Add 1 tablespoon of Coast Spas Non-Chlorine Sanitizer.
4. Add 6 tablespoons of 27% Hydrogen Peroxide (Coast Spas Oxidizer) to help oxidize and clarify the water.

COAST FRESHE COLD PLUNGE

OWNER'S MANUAL

RESIDENTIAL

2026

Daily Water Care

1. Wipe down the plunge surface and clean the drain covers using a soft sponge.
2. Test Hydrogen Peroxide levels using your provided test kit.
3. Add 27% Hydrogen Peroxide (Coast Spas Oxidizer) as needed based on your readings, ideally once in the morning and once at the end of the day.
4. Check and adjust sanitizer, pH, and alkalinity levels according to your test results.

Note: Consistent daily care helps maintain crystal-clear water, protects internal components, and ensures a safe experience for every user.

1. Hydrogen Peroxide (H₂O₂) Levels

Use 27% Hydrogen Peroxide Solution as your primary oxidizer. Check H₂O₂ levels regularly and adjust according to the chart below.

Hydrogen Peroxide (PPM)	Amount of 27% H ₂ O ₂ to Add
0–20 PPM	8 Tbsp
21–40 PPM	7 Tbsp
41–60 PPM	5 Tbsp
61–80 PPM	4 Tbsp
81–100 PPM	3 Tbsp
101+ PPM	No addition required

Note: Allow water to circulate for at least 30 minutes after adding hydrogen peroxide before retesting levels.

2. Sanitizer Levels

Maintain sanitizer levels using Coast Spa Sanitizer (non-chlorine) to ensure safe and clear water.

Sanitizer Reading (PPM)	Action
0 PPM	Add 4 tsp Coast Spa Sanitizer
15 PPM	Add 1 tsp Coast Spa Sanitizer
30–50 PPM	Leave as is
Over 50 PPM	Drain and refill with fresh water

Note: If sanitizer levels remain high after 24 hours, consider partial water replacement to restore balance.

3. pH Balance

The ideal pH range for the Coast Freshe Cold Plunge Residential is 7.2 to 7.8.

Maintaining this range prevents corrosion, scale formation, and skin irritation.

pH Reading	Action
7.0 or below	Add 1 Tbsp Coast Spa Up
7.2–7.3	Add 2 tsp Coast Spa Up
7.4–7.9	Leave as is
8.0 or above	Use Coast Spa Down

! Important: Always adjust alkalinity first before correcting pH levels.

4. Total Alkalinity

Total alkalinity stabilizes pH and prevents erratic water chemistry.

Target range: 80–120 PPM

Alkalinity Reading (PPM)	Action
0–20	Add 4 Tbsp Coast Spa Up
21–40	Add 3 Tbsp Coast Spa Up
41–60	Add 1 Tbsp Coast Spa Up
61–80	Add 1 tsp Coast Spa Up
81–120	Leave as is
180 or above	Use Coast Spa Down

COAST FRESHE COLD PLUNGE RESIDENTIAL

WATER CLARITY TROUBLESHOOTING

PROBLEM	PROBABLE CAUSE	POTENTIAL SOLUTIONS
Water Odor	<ul style="list-style-type: none"> <input type="checkbox"/> Improper sanitization <input type="checkbox"/> Excessive organics in water <input type="checkbox"/> pH is too low 	<ul style="list-style-type: none"> <input type="checkbox"/> Add sanitizer <input type="checkbox"/> Shock unit with sanitizer <input type="checkbox"/> Adjust pH
Chlorine Odor	<ul style="list-style-type: none"> <input type="checkbox"/> Chloramines are too high <input type="checkbox"/> pH is too low 	<ul style="list-style-type: none"> <input type="checkbox"/> Shock unit with sanitizer <input type="checkbox"/> Adjust pH
Musty Odor	<ul style="list-style-type: none"> <input type="checkbox"/> Bacteria or Algae growth 	<ul style="list-style-type: none"> <input type="checkbox"/> Shock unit with sanitizer <input type="checkbox"/> Drain and refill the water
Scale	<ul style="list-style-type: none"> <input type="checkbox"/> Total alkalinity is too high <input type="checkbox"/> pH is too high <input type="checkbox"/> High calcium content in water 	<ul style="list-style-type: none"> <input type="checkbox"/> Adjust total alkalinity <input type="checkbox"/> Adjust pH <input type="checkbox"/> Use stain and scale product
Stain	<ul style="list-style-type: none"> <input type="checkbox"/> Total alkalinity is too low <input type="checkbox"/> pH is too low <input type="checkbox"/> High metal content in water 	<ul style="list-style-type: none"> <input type="checkbox"/> Adjust alkalinity <input type="checkbox"/> Adjust pH <input type="checkbox"/> Use stain and scale product
Cloudy Water	<ul style="list-style-type: none"> <input type="checkbox"/> Poor filtration <input type="checkbox"/> pH is too high <input type="checkbox"/> Hardness is too high <input type="checkbox"/> Total alkalinity is too high <input type="checkbox"/> Suspended particles 	<ul style="list-style-type: none"> <input type="checkbox"/> Clean filter <input type="checkbox"/> Adjust pH <input type="checkbox"/> Adjust hardness <input type="checkbox"/> Adjust total alkalinity <input type="checkbox"/> Drain and refill the water
Algae Growth	<ul style="list-style-type: none"> <input type="checkbox"/> pH is too high <input type="checkbox"/> Sanitizer is too low 	<ul style="list-style-type: none"> <input type="checkbox"/> Adjust pH <input type="checkbox"/> Shock unit with sanitizer <input type="checkbox"/> Adjust sanitizer level
Eye Irritation	<ul style="list-style-type: none"> <input type="checkbox"/> pH is too low <input type="checkbox"/> Sanitizer is too low 	<ul style="list-style-type: none"> <input type="checkbox"/> Adjust pH <input type="checkbox"/> Shock unit with sanitizer <input type="checkbox"/> Adjust sanitizer level
Skin Rash/Irritation	<ul style="list-style-type: none"> <input type="checkbox"/> Free chlorine level too high <input type="checkbox"/> Unsanitary water 	<ul style="list-style-type: none"> <input type="checkbox"/> Adjust chlorine level <input type="checkbox"/> Shock unit with sanitizer <input type="checkbox"/> Adjust sanitizer level

COAST FRESHE COLD PLUNGE RESIDENTIAL

OWNER'S MANUAL

2026

DRAINING AND WINTERIZING

The Coast Freshe Cold Plunge Residential is designed to withstand various weather conditions but is not rated for freezing temperatures. If the temperatures in the area drop to 32°F (0°C) or lower, you must winterize the unit to prevent damage.

If the temperature is expected to stay below freezing for more than 12 hours, follow these steps to properly store and protect your Cold Plunge system:

STEP BY STEP DRAINING AND WINTERIZATION PROCESS

Step 1: Power Down the System

- Turn off the chiller and unplug it from the power source.
- Ensure the system is powered down before proceeding.

Step 2: Open the External Drain

- Locate the external drain valve underneath the chiller.
- Remove cap and turn the ball valve to the open position to allow water to drain.

Step 3: Manage Water Drainage

- If needed, connect a garden hose redirect water to drainage.
- Ensure to comply with local drainage regulations.

Step 4: Fully Drain the Plunge

- Even after water stops flowing from the external drain, some water may remain in the internal plumbing.
- Use a shop vac to remove any remaining water.

Step 5: Disconnect and clean the Sand Filter

- Turn off the pump and disconnect power.
- Remove the drain plug and let all water drain from the filter tank.
- Detach hoses and the multiport valve, then store them indoors.
- Leave the tank open and cover it loosely to prevent trapped moisture and freezing.

Step 6: Store the Coast Freshe Cold Plunge Residential Properly

- Once fully drained, clean the interior and exterior using a mild cleaning solution to remove bacteria, residue, and other contaminants.
- Use the cover for safety and protection from dust and debris.
- Final Check
- Confirm that all water has been removed from the system, including the filter housing.
- Use a sponge or towel to soak up any remaining moisture.

By following these steps, you can prevent damage and extend the lifespan of your Coast Freshe Cold Plunge Residential, ensuring it remains in optimal condition for future use.

⚠ WARNING: Always follow proper winterization steps and ensure your Coast Freshe Cold Plunge Residential is prepared correctly for freezing conditions

⚠ IMPORTANT WARRANTY INFORMATION: Please be aware that damage caused by freezing temperatures or improper water chemistry is not covered under the warranty.

Cold Weather Monitoring & Winterization

When outdoor temperatures approach freezing (32°F / 0°C), monitor your Coast Freshe Cold Plunge Residential daily to ensure proper flow. If temperatures remain below freezing for 12 hours or longer, you must fully drain and winterize the Coast Freshe Cold Plunge Residential, including the filter housing and chiller, to prevent damage.

Liability and Safety Notice

LIABILITY DISCLAIMER: Coast Spas is not responsible for repairs or replacement to any damages that occur due to the Coast Freshe Cold Plunge Residential left in freezing conditions without being properly drained/ stored. Customer may contact selling dealer/ service provider for repairs, but any damage caused by freezing will not be covered under warranty.

ASSUMPTION OF RISK: By using your Coast Freshe Cold Plunge Residential, you accept all risks related to its operation and maintenance. This includes the risk of injury, illness, or property damage that may result from improper use, poor water care, or not following the safety and maintenance instructions provided in this manual.

COMMERCIAL OPERATOR RESPONSIBILITIES

If your unit is used in a commercial or public setting, the facility owner or operator must:

- Test and record water quality daily.
- Maintain proper chemical balance as required by local health and safety regulations (e.g., BC Pool Regulations, CSA C22.2 No. 218); and
- Ensure that only trained personnel operate and maintain the unit.

Coast Spas' warranty and liability coverage apply only when the unit is used and maintained according to Coast Spas' instructions and by qualified personnel.

COAST FRESHE COLD PLUNGE RESIDENTIAL

INDEMNIFICATION: By installing or operating this unit, the owner or operator agrees to protect and hold Coast Spas harmless from any claims, damages, or losses that result from misuse, unauthorized changes, or failure to maintain safe operating conditions.

THIRD PARTY EQUIPMENT DISCLAIMER: If any third-party components (such as filters, chillers, dosing systems, or automation equipment) are added or modified by others, Coast Spas cannot be held responsible for any damage, malfunction, or injury that may result from those additions.

Winter Preparation Guide

Coast Freshe Cold Plunge Residential

Proper winter preparation ensures peak performance and protects your Coast Freshe Cold Plunge Residential from cold-weather damage. Follow the guidelines below to maintain safe, reliable operation throughout the winter season.

1. Maintain Clean and Efficient Filtration.

A clean filter ensures efficient water circulation and performance.

- Inspect the filter regularly for debris or buildup.
- Backwash when pressure rises 5–10 psi above normal. Rinse for 30 seconds, then return to FILTER. Replace sand every 3–5 years.

2. Ensure Continuous Water Flow

Adequate water movement helps prevent freezing and system shutdown.

- Check flow daily to confirm a steady stream of water.
- If flow becomes restricted, troubleshoot immediately.
- If flow cannot be restored, fully drain and winterize the unit to prevent freezing damage.

3. Monitor Freezing Conditions

Cold temperatures can affect system performance.

- Stay aware of local weather conditions.
- If temperatures are forecast to drop below 32°F (0°C) for more than 12 hours, take preventative action.

4. Winter Operations Options

- **Using the unit:** Set water temperature to 50°F (10°C) or higher.
- **Not using the unit:** Fully drain and winterize according to the Owner's Manual.

5. Full Drain for Freeze Protection

If freezing temperatures persist:

- Fully drain the unit to prevent ice formation inside plumbing or equipment.
- Proper drainage ensures no residual water remains that could cause damage.

6. Severe Weather or Power Outage Preparation

- Drain the unit if a storm or outage is expected.
- Store chiller and filter indoors in a warm location.
- Follow Owner's Manual for detailed winterization instructions.

7. Extended Absence During Freezing Weather

- Drain and winterize if away for more than 24 hours in freezing conditions.
- Store components indoors to protect from extreme cold.

By following these winter maintenance steps, you can protect your Coast Freshe Cold Plunge Residential from freezing conditions and ensure reliable performance throughout the winter season and beyond.

COAST FRESHE COLD PLUNGE RESIDENTIAL

AUTO DOSING SYSTEM

Auto Dosing System Maintenance

The Automatic Dosing System is a built-in feature of the Coast Spas Coast Freshe Cold Plunge Residential. It is designed to automate water care by monitoring and adjusting the levels of chlorine and pH, helping ensure water quality remains clean, safe, and compliant with health standards, especially in commercial or high-usage environments.

Accessing the System:

Locate the access door. It's discreetly tucked away to avoid becoming a tripping hazard. Remove the door, simply pull it off. No tools or force are required. It's held in place by magnets for easy access.

Chemical Containers

The System uses two chemical containers:

- One for chlorine
- One for pH+ (pH increaser)

Refilling Chemicals

1. Remove the chemical bottle from the system.
2. Take off the tap and protective cap.
3. Refill with the appropriate chemical.

⚠ Important: Never mix chlorine and pH+ chemicals, as this can create a hazardous reaction.

4. Replace the cap securely.
5. Return the bottle to its slot in the system.
6. Close the access panel.


⚠ Important: Regularly check chemical levels and refill as needed.

⚠ Important: Inspect sensors periodically for debris or scaling. Clean gently with a soft cloth if necessary.

⚠ Important: Do not mix chemicals under any circumstance. Keep handling and storage strictly separated.

⚠ Important: For commercial use, follow all applicable local health and safety regulations related to water quality management, chemical storage, and dosing system operation.

⚠ Important: Confirm that the dosing system is connected via Ethernet if using cloud-based monitoring. This enables real-time performance tracking and alert notifications on compatible smart devices.



COAST FRESHE COLD PLUNGE RESIDENTIAL

Water Sand Filter Installation Instruction

Unbox and Prepare Components. Carefully remove all components from the box. Your Coast Freshe Cold Plunge Residential came with a sand filter.

Install the Filter

1. Remove the access door by gently pulling the top edge outward to release the magnets, then lift the ventilation screens upward to remove.
2. Position the sand filter in the designated area inside the equipment bay.
3. Connect the multiport valve to the filter tank and ensure the gasket is seated properly.

Proper Set up

1. Fill the tank halfway with water to cushion the sand.
2. Add the correct amount of No. 20–40 silica sand slowly into the tank.
3. Attach the multiport valve securely and hand-tighten clamps; do not overtighten.

⚠ Important Notice: Note the Flow Rate

- During installation, observe the initial water flow rate.
- A decrease in flow indicates the need for filter cleaning.
- Proper flow is essential for Coast Freshe Cold Plunge Residential performance.

Filter Maintenance

The Filter replacement depends on the Coast Freshe Cold Plunge Residential usage and maintenance. Please contact your closest Coast Spas authorized dealership for more information.

- Check the filter weekly.
- If you notice reduced water flow, clean the filter immediately.
- Never operate the chiller with inadequate water flow.



Do not use the Coast Freshe Cold Plunge Residential without a filter installed.

If you notice no water flow or suspect that the flow is not normal, immediately power off and unplug the Coast Freshe Cold Plunge Residential. Contact the selling dealer's service department for assistance.

Damage caused by slow flow due to improper set up or lack of maintenance is not covered under the warranty. Always ensure proper installation and regular filter cleaning to maintain optimal performance.

Failure to clean the filter housing and replace the filter regularly, leading to slow or no water flow, may result in chiller damage. Coast Spas is not responsible for damage caused by improper maintenance.

IMPORTANT NOTICE

The Filter must be cleaned or replaced when required. Regular maintenance ensures optimal performance and prevents damage to the chiller.

The need for replacement may vary based on the following factors:

- Usage frequency – More frequent use may require more regular cleaning.
- Personal hygiene – Residues from lotions, oils, or sweat can clog the filter faster.
- Environmental conditions – High pollen levels, dust, or outdoor placement may necessitate more frequent cleaning.

To maintain proper water flow and efficiency, always inspect the filter weekly and maintain as needed.

COAST FRESHE COLD PLUNGE RESIDENTIAL

Coast Freshe Cold Plunge How-To Videos



Start-up and Filling



Care & Maintenance



Draining Instructions

For more How-To Videos you may click the link below or scan the QR code.

https://www.youtube.com/playlist?list=PLGuCzEgLVx0nfSIGoQzRr9a33C_Rvr_m8





WORLD'S BEST BUILT SPAS